



Durameleon® Plus

The illuminated Durameleon® Plus Arch Series is built to perform – with the available patented Twist-N-Flip™ action of the top and side nozzles. Delivering the most complete application coverage ever from one arch, this feature uses a single air cylinder to synchronize all 3 manifolds, for complete coverage of the vehicle front, sides, top, mirrors, and back – every time.

In addition the Durameleon Plus also features three strategically placed Foam Bullets, one located on each manifold. These Foam Bullets run on an independent chemical feed from the manifolds, which enables operators to deliver two different applications, at the same time

To further promote your image, LED-illuminated manifold lenses are available in a bright translucent look and vivid backlit colors – or choose optional manifold covers in a deep black color. And branding options include left and right 'corner' signs and a center pendant perfect for prominent service announcement or logo decals.

What's more, the stainless steel manifolds allow flexible chemical use, with configurations available for Presoak, Wax, Rinse and Spot-Free.

Durameleon® Plus



2 Applications in 1 Great Arch

With dual chemical feeds, the Durameleon Plus's flipping Foam Bullets® enable you to simultaneously run a second application through them versus the manifold's application



Covers the front, sides, top, mirrors & back

'Twist & Flip'™ action synchronizes all 3 illuminated Foam Bullets® with just 1 air cylinder



Lighted manifolds & bullets attract attention

Attract attention with the impressive light show



Cuts maintenance & increases your uptime

With durable stainless steel manifolds, and a grease-free bearing design



LED 'Wall Washer' Light Bar

To illuminate the applied product & vehicle



Builds your brand & promotes your services

With illuminated center pendant and corner signs

SPECIFICATIONS

Physical Configurations:

Component Height	12' 4"
Component Width	9'
Minimum Tunnel Length Required	1' 6"

Utility Requirements:

Electrical	(1) 120 VAC output from Controller to air panel & LED Control Box.
Air	(1) SCFM @ 100 PSI air flow (Minimum)
Water	3/4" feed @ 12 PGM @ 40 PSI (Minimum)

CUSTOM GRAPHICS

Choose your backlit center pendant and shoulder decals.



Belanger
1001 Doheny Court
P.O. Box 5470
Northville, MI 48167-5470 USA
belangerinc.com | 248-349-7010

BELANGER 

Inspired by You. Built by Belanger.

PART OF
OPW 
VEHICLE WASH
SOLUTIONS
a **DOVER** company