



MiniFlex™

'BIG ON PERFORMANCE AND RELIABILITY — SMALL ON TUNNEL SPACE REQUIREMENTS'

The MiniFlex™ top wheel from Belanger requires less than 7' of tunnel space by utilizing our patented 'gator gear' design for a compact footprint. Add another top wheel for more top cleaning or add extra-service revenue generating equipment in less tunnel space than two conventional top wheels.

As a dedicated horizontal surface washer, the MiniFlex excels at cleaning hoods, roofs and trunk lids – all while providing a super-quiet customer experience. The uniquely shaped Neo-Tex™ closed-cell foam wash 'fingers' provide superior wash penetration with vastly reduced in-car noise levels. The uniquely designed counterweight and built-in dampener help the wheel maintain proper pressure and smooth movement during the washing process, for optimal cleaning performance.

Because the MiniFlex is a key contributor in achieving a clean car, it's built for maximum uptime and dependable operation.

FEATURES & BENEFITS

Advanced Top Surface Washer

Delivers contoured cleaning results to all horizontal surfaces including hoods, roofs, and trunk lids

Smooth Movement & Control

The counterweight and built-in dampener design helps the wheel maintain proper pressure and smooth movement during the wash process for exception wash results



'Gator Gear' Design (Patented)

Enables the MiniFlex to have an ultra-compact design that requires less tunnel space

Uniquely Shaped Neo-Tex™

Provides superior wash penetration with a significantly quieter in-car wash experience

REQUIREMENTS

Physical Examples

Component Height	10' 9 5/8"
Component Width	13'
Tunnel Length Required	6' 10 3/8"

Utility Examples

Electrical	3 Phase, 60Hz, (1) HP motor @ 208-230/460V or 50Hz @ 575V for hub
Water	4 GPM @ 40 PSI
Pneumatic	1.2 CFM @ 90 PSI minimum, 120 PSI maximum

COLOR OPTIONS

Choose from six vivid Neo-Tex™ colors



Belanger

31840 Enterprise Drive, Bldg 5
Livonia, MI 48150 USA
belangerinc.com | 248-349-7010